

## WMD-06 motorized swing gate with swing panel AGG-900 for indoor application



operating  
voltage




power  
consumption



passage  
directions



persons/min



temperature  
range



protection rating



motor drive



scheme



3D-presentation

Operating voltage	24 V DC
Power consumption	105 W
Consumption current	4.4 A
Number of passage directions	2
Throughput rate (in the single passage mode)	12 persons/min
Dimensions (length×width×height)	795×147×1012 mm
Passageway width	700 mm
Operating temperature range	from +1 °C to +50 °C
IP Code	IP41

Gate post – stainless steel.



stainless steel

Swing panel – 10 mm tempered glass.



The warranty period is 5 (five) years from the date of sale of the product.





# REVROY

Solutions For Controlled Access

## CONTACT

Ravi@revroy.com

+91 080 41302021, +91 080 41571225, +91 9840294082

### South

Prem@Revroy.Com  
+919900013769

### West

RevroySales1@Revroy.Com  
+918792918954

### Tech Support

Techsupport@Revroy.Com  
+918792918953

### SALES OFFICE

No.#13, Hamdh Court Building,  
Mother Teresa Road, Austin Town,  
Bangalore-560 047, India

### FACTORY

Plot No 143-B, Bommasandra Industrial Area  
Bangalore-560099, Karnataka. India.  
+91 80 41658921

“Finest from the very best from around the world”



[www.revroy.com](http://www.revroy.com)