



TTR-10AB Motorized tripod turnstile for outdoor application, with automatic anti-panic function




operating
voltage



passage
directions



persons/min



temperature
range



IP Code



"anti-panic"
barrier arms



motor drive



scheme

TTR-10AB Motorized tripod turnstile is designed for floor mounting and is used as a compact blocking device to control the stream of people at the entrances of industrial enterprises, banks, administrative offices, shops, railway stations, airports.

- Motor drive ensures smooth turn of barrier arms
- Compact design
- Automatic "Anti-panic" barrier arms
- Weatherproof design



Delivery set:

- turnstile with built-in electronics
- flywheel with automatic "Anti-Panic" barrier arms
- stand for floor mounting
- remote control panel

In addition to the option for floor mounting it is also possible to fix TTR- 10A on the wall or transport handrails.

The turnstile allows you to clear the passageway quickly in case of emergency, or in case of power loss.

It is possible to control the turnstile both from the access control system and by using a remote control or wireless remote-control device (sold separately).

A control board is effectively placed inside the turnstile housing. The resetting mechanism moves the barrier arms to the initial position after each pass. Smooth turn of the barrier arms is carried out by the built-in motor drive.

A special Fire Alarm control input allows you to connect a device that sends command for the emergency unlock (for example, from a fire alarm).

It is possible to connect the passageway control sensor and siren to the turnstile.

To ensure quick and convenient passage of people, it is recommended to install one turnstile for every 500 people working in one shift, or on the basis of a peak load of 30 people per minute.

Operating voltage	24 V DC
Power consumption	150 W
Consumption current	5.5 A
Number of passage directions	2
Throughput rate (in the single passage mode)	30 persons/min
Throughput rate (in the free passage mode)	60 persons/min
Dimensions (length×width×height)	800×760×1055 mm
Passageway width	500 mm
Operating temperature range	from -40 °C to +55 °C
IP Code	IP54
Mean lifetime	8 years
Mean time to failure	3 000 000 passages

Turnstile housing, barrier arms



stainless steel

The warranty period is 5 (five) years from the date of sale of the product.





REVROY

Solutions For Controlled Access

CONTACT

Ravi@revroy.com

+91 080 41302021, +91 080 41571225, +91 9840294082

South

Prem@Revroy.Com
+919900013769

West

RevroySales1@Revroy.Com
+918792918954

Tech Support

Techsupport@Revroy.Com
+918792918953

SALES OFFICE

No.#13, Hamdh Court Building,
Mother Teresa Road, Austin Town,
Bangalore-560 047, India

FACTORY

Plot No 143-B, Bommasandra Industrial Area
Bangalore-560099, Karnataka. India.
+91 80 41658921

“Finest from the very best from around the world”



www.revroy.com